



HASTINGS

TOUGH GUY™ RACING RINGS



TOUGH GUYS FINISH FIRST!™

HASTINGS TOUGH GUY RACING RINGS by Diameter

SET NO.	CYL.	DIAMETER	RING WIDTHS	STYLE	OIL RING TENSION	SET NO.	CYL.	DIAMETER	RING WIDTHS	STYLE	OIL RING TENSION
SC5558	4	Std. 2.9530 .010 2.9630 .020 2.9730 .030 2.9830 .040 2.9930 .060 3.0130	1.2, 1.5, 2.8	5	Std.			.005 3.8800 .030 3.9050 .035 3.9100 .065 3.9400			
2M5546	4	Std. 3.1875 .005 3.1925 .045 3.2325	5/64, 5/64, 5/32	1	Std.	2M5503	8	Std. 3.8750 .030 3.9050 .060 3.9350	5/64, 5/64, 3/16	1	Low
2M5545	4	Std. 3.1875 .005 3.1925 .035 3.2225 .045 3.2325	1/16, 5/64, 5/32	1	Std.	2M5522	8	Std. 3.8750 .005 3.8800 .030 3.9050 .035 3.9100 .060 3.9350 .065 3.9400	1/16, 1/16, 1/8	1	Std.
SC5572	4	Std. 3.1890 .010 3.1990 .020 3.2090 .030 3.2190 .040 3.2290	1.0, 1.2, 2.8	5	Std.	2M5575	8	Std. 3.9100 .030 3.9400 .040 3.9500 .060 3.9600	1/16, 1/16, 3/16	1	Std.
2C5573	4	Std. 3.2680 .010 3.2780 .020 3.2880 .030 3.2980 .040 3.3080 .060 3.3275	1.5, 1.5, 3.0	2	Std.	2M5507	8	Std. 3.9375	5/64, 5/64, 3/16	1	Std.
SC8513	4	Std. 3.3070 .020 3.3275 .040 3.3475	1.0, 1.2, 2.8	5	Std.	SM5587	8	Std. 4.0000 .005 4.0050 .010 4.0100 .020 4.0200 .025 4.0250 .035 4.0350 .040 4.0400 .045 4.0450 .055 4.0550 .060 4.0600 .065 4.0650 .070 4.0700 .080 4.0800 .100 4.1000	.043, .043, 3.0	3	Std.
SC5556	4	Std. 3.4450 .010 3.4550 .020 3.4650 .030 3.4750 .040 3.4850 .060 3.5050	1.2, 1.2, 3.0	5	Std.	SM8527	8	Std. 4.0000 .005 4.0050 .025 4.0250 .035 4.0350 .045 4.0450 .065 4.0650 .080 4.0800	.043, 1/16, 3/16	3	Std.
2M5544	4	Std. 3.5750 .005 3.5800 .025 3.6000 .030 3.6050 .035 3.6100	1/16, 1/16, 1/8	1	Std.	SM8537	8	Std. 4.0000 .005 4.0050 .025 4.0250 .035 4.0350 .045 4.0450 .065 4.0650 .080 4.0800	.043, 1/16, 3/16	3	Low
2M5547	8	Std. 3.7360 .035 3.7710 .045 3.7810 .065 3.8010	5/64, 5/64, 3/16	1	Std.	C5530	8	Std. 4.0000 .030 4.0300 .040 4.0400 .060 4.0600	1.5, 1.5, 4.0	7	Std.
2M5548	8	Std. 3.7360 .035 3.7710 .065 3.8010	5/64, 5/64, 3/16	1	Low	CM5530	8	Std. 4.0000 .030 4.0300 .040 4.0400 .060 4.0600	1.5, 1.5, 4.0	8	Std.
2M5567	8	Std. 3.7360 .020 3.7560 .030 3.7660 .035 3.7710 .040 3.7760 .060 3.7960	1/16, 1/16, 3/16	1	Std.	2M5535	8	Std. 4.0000 .005 4.0050 .030 4.0300 .035 4.0350 .040 4.0400 .045 4.0450	1.5, 1.5, 4.0	1	Std.
2M5527	4	Std. 3.7800 .020 3.8000 .030 3.8100 .035 3.8150 .040 3.8200 .045 3.8250 .060 3.8400	1/16, 1/16, 3/16	1	Std.						
2M5506	8	Std. 3.8750	5/64, 5/64, 3/16	1	Std.						



Style

- 1 Ductile Iron, Torsional, Plasma Moly
- 2 Ductile Iron, Barrel Face, Chrome Plated
- 3 Steel, Torsional, Plasma Moly
- 4 Steel, Torsional, Plasma Moly
- 5 Steel, Barrel Face, Chrome Plated
- 6 Ductile Iron, Torsional, Plasma Moly
- 7 CLAIMER Cast Iron, Torsional, Phosphate Coated
- 8 CLAIMER Cast Iron, Torsional, Plasma Moly

Top

- 1 Cast Iron, Reverse Twist Torsional
- 2 Cast Iron, Reverse Twist Torsional
- 3 Cast Iron, Reverse Twist Torsional
- 4 Cast Iron, Napier
- 5 Cast Iron, Reverse Twist Torsional
- 6 Ductile iron, Napier
- 7 Cast Iron, Reverse Twist Torsional
- 8 Cast Iron, Reverse Twist Torsional

2nd

Oil

- 1 Hastings Patented Flex-Vent
- 2 Hastings Patented Flex-Vent
- 3 Hastings Patented Flex-Vent
- 4 Hastings Patented Flex-Vent
- 5 Hastings Patented Flex-Vent
- 6 Hastings Patented Flex-Vent
- 7 Hastings Patented Flex-Vent
- 8 Hastings Patented Flex-Vent

CALL 269-945-2491
800-776-1088

428

Visit us at www.hastingsracing.com

HASTINGS TOUGH GUY RACING RINGS by Diameter

SET NO.	CYL.	DIAMETER	RING WIDTHS	STYLE	OIL RING TENSION	SET NO.	CYL.	DIAMETER	RING WIDTHS	STYLE	OIL RING TENSION
C5540	8	.060 4.0600	1.5, 1.5, 3.0	7	Std.	CM5521	8	.020 4.0200	1/16, 1/16, 1/8	8	Std.
		.065 4.0650						.030 4.0300			
		Std. 4.0000						Std. 4.0000			
		.020 4.2000						.030 4.0300			
		.030 4.3000						.035 4.0350			
		.040 4.0400						.040 4.0400			
CM5540	8	.060 4.0600	1.5, 1.5, 3.0	8	Std.	2M5521	8	.045 4.0450	1/16, 1/16, 1/8	1	Std.
		Std. 4.0000						.060 4.0600			
		.020 4.2000						.065 4.0650			
		.030 4.3000						Std. 4.0000			
		.040 4.0400						.005 4.0050			
		.060 4.0600						.010 4.0100			
2M5540	8	Std. 4.0000	1.5, 1.5, 3.0	1	Std.	2M8571	8	.020 4.0200	1/16, 1/16, 1/8	6	Std.
		.005 4.0050						.025 4.0250			
		.025 4.0250						.030 4.0300			
		.030 4.0300						.035 4.0350			
		.035 4.0350						.040 4.0400			
		.040 4.0400						.045 4.0450			
		.045 4.0450						.060 4.0600			
		.060 4.0600						.065 4.0650			
		.065 4.0650						Std. 4.0000			
		.085 4.0850						.030 4.0300			
		.090 4.0900						.035 4.0350			
		.095 4.0950						.040 4.0400			
2M5538	8	Std. 4.0000	1/16, 1/16, 3.0	1	Std.	C5532	8	.040 4.0400	1/16, 1/16, 3/16	7	Std.
		.005 4.0050						Std. 4.0000			
		.010 4.0100						.020 4.0200			
		.020 4.0200						.030 4.0300			
		.025 4.0250						.040 4.0400			
		.030 4.0300						.060 4.0600			
		.035 4.0350						Std. 4.0000			
		.040 4.0400						.020 4.0200			
		.060 4.0600						.030 4.0300			
		.065 4.0650						.035 4.0350			
		.075 4.0750						.040 4.0400			
		.103 4.1025						.045 4.0450			
C5531	8	Std. 4.0000	5/64, 5/64, 3/16	7	Std.	2M8542	8	.060 4.0600	1/16, 1/16, 3/16	6	Std.
		.030 4.0300						Std. 4.0000			
		.040 4.0400						.005 4.0050			
		.060 4.0600						.030 4.0300			
CM5531	8	Std. 4.0000	5/64, 5/64, 3/16	8	Std.	SN8575	8	.035 4.0350	1/16, 1/16, 3/16	PVD	Reduced
		.030 4.0300						Std. 4.0000			
		.040 4.0400						.005 4.0050			
		.060 4.0600						.035 4.0350			
2M5502	4	Std. 4.0000	5/64, 5/64, 3/16	1	Std.	2M5523	8	.045 4.0450	1/16, 1/16, 3/16	1	Std.
		.020 4.0200						Std. 4.0000			
		.030 4.0300						.005 4.0050			
		.060 4.0600						.010 4.0100			
2M5508	8	Std. 4.0000	5/64, 5/64, 3/16	1	Std.	2M5504	8	.025 4.0250	5/64, 5/64, 3/16	1	Low
		.005 4.0050						.025 4.0250			
		.020 4.0200						.030 4.0300			
		.025 4.0250						.035 4.0350			
		.030 4.0300						.040 4.0400			
		.035 4.0350						.045 4.0450			
		.040 4.0400						.060 4.0600			
		.045 4.0450						.065 4.0650			
		.060 4.0600						Std. 4.0000			
		.065 4.0650									
		Std. 4.0000									

Style

- 1 Ductile Iron, Torsional, Plasma Moly
- 2 Ductile Iron, Barrel Face, Chrome Plated
- 3 Steel, Torsional, Plasma Moly
- 4 Steel, Torsional, Plasma Moly
- 5 Steel, Barrel Face, Chrome Plated
- 6 Ductile Iron, Torsional, Plasma Moly
- 7 CLAIMER Cast Iron, Torsional, Phosphate Coated
- 8 CLAIMER Cast Iron, Torsional, Plasma Moly

2nd

- Cast Iron, Reverse Twist Torsional
- Cast Iron, Reverse Twist Torsional
- Cast Iron, Reverse Twist Torsional
- Cast Iron, Napier
- Cast Iron, Reverse Twist Torsional
- Ductile Iron, Napier
- Cast Iron, Reverse Twist Torsional
- Cast Iron, Reverse Twist Torsional

Oil

- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent



HASTINGS TOUGH GUY RACING RINGS by Diameter

SET NO.	CYL.	DIAMETER	RING WIDTHS	STYLE	OIL RING TENSION	SET NO.	CYL.	DIAMETER	RING WIDTHS	STYLE	OIL RING TENSION
2M5505	8	.070 4.0700	1/16, 1/16, 3/16	1	Low	SM8557	8	.060 4.1850	.043, 1/16, 3/16	3	Low
		.080 4.0800									
		Std. 4.0000									
		.005 4.0050									
		.010 4.0100									
		.025 4.0250									
		.030 4.0300									
		.035 4.0350									
		.045 4.0450									
		.060 4.0600									
		.065 4.0650									
		Std. 4.0000									
		.005 4.0050									
		.030 4.0300									
		.035 4.0350									
2M8543	8	.060 4.0600	1/16, 1/16, 3/16	6	Low	SM8547	8	.060 4.1850	.043, 1/16, 3/16	3	Std.
		.065 4.0650									
		Std. 4.0000									
		.005 4.0050									
		.030 4.0300									
		.035 4.0350									
		.040 4.0400									
		.045 4.0450									
		.060 4.0600									
		.065 4.0650									
		Std. 4.0400									
		.030 4.0300									
		.035 4.0350									
		.040 4.0400									
		.045 4.0450									
2M5561	8	.065 4.0650	5/64, 5/64, 3/16	1	Std.	C5533	8	.060 4.1850	5/64, 5/64, 3/16	7	Std.
		Std. 4.0400									
		.030 4.0700									
		.060 4.1000									
		Std. 4.0500									
		.005 4.0550									
		.030 4.0800									
		.035 4.0850									
		.040 4.0900									
		.060 4.1100									
		.065 4.1150									
		Std. 4.0625									
		.005 4.0675									
		.035 4.0975									
		.065 4.1275									
2M5525	8	.065 4.1275	1/16, 1/16, 3/16	1	Std.	CM5533	8	.060 4.1850	5/64, 5/64, 3/16	8	Std.
		Std. 4.0500									
		.005 4.0550									
		.030 4.0800									
		.035 4.0850									
		.040 4.0900									
		.060 4.1100									
		.065 4.1150									
		Std. 4.0625									
		.005 4.0675									
		.035 4.0975									
		.065 4.1275									
		Std. 4.0925									
		.005 4.0975									
		.030 4.1250									
2M5511	8	.035 4.1275	5/64, 5/64, 3/16	1	Std.	2M5513	8	.060 4.1850	5/64, 5/64, 3/16	1	Std.
		.060 4.1550									
		.065 4.1575									
		Std. 4.1200									
		.005 4.1250									
		.030 4.1500									
		.035 4.1550									
		.065 4.1850									
		Std. 4.1200									
		.005 4.1250									
		.030 4.1500									
		.035 4.1550									
		.065 4.1850									
		Std. 4.1200									
		.005 4.1250									
2M5512	8	.065 4.1850	1/16, 1/16, 1/8	1	Std.	2M5501	8	.060 4.1850	1/16, 1/16, 1/8	1	Std.
		Std. 4.1200									
		.005 4.1250									
		.030 4.1500									
		.035 4.1550									
		.065 4.1850									
		Std. 4.1200									
		.005 4.1250									
		.030 4.1500									
		.035 4.1550									
		.065 4.1850									
		Std. 4.1200									
		.005 4.1250									
		.030 4.1500									
		.035 4.1550									
2M5524	8	.065 4.1850	1/16, 1/16, 3/16	1	Std.	C5534	8	.060 4.1850	1/16, 1/16, 3/16	7	Std.
		Std. 4.1200									
		.005 4.1250									
		.030 4.1500									
		.035 4.1550									
		.065 4.1850									
		Std. 4.1200									
		.005 4.1250									
		.030 4.1500									
		.035 4.1550									
		.065 4.1850									
		Std. 4.1200									
		.005 4.1250									
		.030 4.1500									
		.035 4.1550									
2M5590	8	.065 4.1850	.043, .043, 3.0	3	Std.	CM5534	8	.060 4.1850	1/16, 1/16, 3/16	8	Std.
		Std. 4.1250									
		.005 4.1300									
		.010 4.1350									
		.015 4.1400									
		.020 4.1450									
		.025 4.1500									
		.030 4.1550									
		.035 4.1600									
		.040 4.1650									
		.045 4.1700									
		.050 4.1750									
		.055 4.1800									
		Std. 4.1250									
		.005 4.1300									
SM5593	8	.065 4.1850	.043, .043, 3.0	3	Std.	2M5529	8	.060 4.1850	1/16, 1/16, 3/16	1	Std.
		Std. 4.1250									
		.005 4.1300									
		.010 4.1350									
		.015 4.1400									
		.020 4.1450									
		.025 4.1500									
		.030 4.1550									
		.035 4.1600									
		.040 4.1650									
		.045 4.1700									
		.050 4.1750									
		.055 4.1800									
		Std. 4.1250									
		.005 4.1300									
.020 4.1450											



Style

- 1 Ductile Iron, Torsional, Plasma Moly
- 2 Ductile Iron, Barrel Face, Chrome Plated
- 3 Steel, Torsional, Plasma Moly
- 4 Steel, Torsional, Plasma Moly
- 5 Steel, Barrel Face, Chrome Plated
- 6 Ductile Iron, Torsional, Plasma Moly
- 7 CLAIMER Cast Iron, Torsional, Phosphate Coated
- 8 CLAIMER Cast Iron, Torsional, Plasma Moly

Top

2nd

- 1 Cast Iron, Reverse Twist Torsional
- 2 Cast Iron, Reverse Twist Torsional
- 3 Cast Iron, Reverse Twist Torsional
- 4 Cast Iron, Napier
- 5 Cast Iron, Reverse Twist Torsional
- 6 Ductile iron, Napier
- 7 Cast Iron, Reverse Twist Torsional
- 8 Cast Iron, Reverse Twist Torsional

Oil

- 1 Hastings Patented Flex-Vent
- 2 Hastings Patented Flex-Vent
- 3 Hastings Patented Flex-Vent
- 4 Hastings Patented Flex-Vent
- 5 Hastings Patented Flex-Vent
- 6 Hastings Patented Flex-Vent
- 7 Hastings Patented Flex-Vent
- 8 Hastings Patented Flex-Vent

CALL 269-945-2491
800-776-1088

430

Visit us at www.hastingsracing.com

HASTINGS TOUGH GUY RACING RINGS by Diameter

SET NO.	CYL.	DIAMETER	RING WIDTHS	STYLE	OIL RING TENSION	SET NO.	CYL.	DIAMETER	RING WIDTHS	STYLE	OIL RING TENSION
		.025 4.1500						.005 4.1700			
		.030 4.1550						.030 4.1950			
		.035 4.1600						.035 4.2000			
		.040 4.1650						.045 4.2100			
		.045 4.1700						.065 4.2300			
		.060 4.1850				2M5526	8	Std. 4.2325	1/16, 1/16, 3/16	1	Std.
		.065 4.1900						.005 4.2370			
2M8559	8	Std. 4.1250	1/16, 1/16, 3/16	6	Low			.010 4.2425			
		.005 4.1300						.015 4.2475			
		.030 4.1550						.020 4.2525			
		.035 4.1600						.025 4.2575			
		.040 4.1650						.030 4.2625			
		.045 4.1700						.035 4.2675			
		.060 4.1850				2M5516	8	Std. 4.2325	5/64, 3/32, 3/16	1	Std.
		.065 4.1900						.005 4.2375			
2M5539	8	Std. 4.1250	1/16, 1/16, 3.0	1	Std.			.035 4.2675			
		.005 4.1300						.065 4.2975			
		.010 4.1350				2M5517	8	Std. 4.2330	1/16, 1/16, 1/8	1	Std.
		.020 4.1450						.005 4.2375			
		.030 4.1550						.030 4.2625			
		.035 4.1600						.035 4.2675			
		.040 4.1650						.065 4.2975			
		Std. 4.1250	1.5, 1.5, 3.0	1	Std.	SM5597	8	Std. 4.2500	.043, .043, 3.0	4	Std.
		.005 4.1300				SM8567	8	Std. 4.2500	.043, 1/6, 3/16	3	Std.
		.010 4.1350				SM8577	8	Std. 4.2500	.043, 1/6, 3/16	3	Low
		.015 4.1400				2M8569	8	Std. 4.2500	1.5, 1.5, 3.0	1	Std.
		.020 4.1450						.030 4.2800			
		.030 4.1550				2M5518	8	Std. 4.2500	5/64, 5/64, 3/16	1	Std.
		.035 4.1600						.005 4.2550			
		.045 4.1700						.030 4.2800			
		.065 4.1900						.035 4.2850			
2M8552	8	Std. 4.1250	1/16, 1/16, 3/16	6	Std.			.040 4.2900			
		.005 4.1300						.045 4.2950			
		.030 4.1550						.060 4.3100			
		.035 4.1600						.065 4.3150			
		.040 4.1650				2M5514	8	Std. 4.2500	5/64, 5/64, 3/16	1	Low
		.045 4.1700						.030 4.2800			
		.060 4.1850						.060 4.3100			
		.065 4.1900				2M5519	8	Std. 4.2500	1/16, 1/16, 3/16	1	Std.
2M5510	8	Std. 4.1250	1/16, 1/16, 3/16	1	Low			.005 4.2550			
		.005 4.1300						.020 4.2700			
		.020 4.1450						.030 4.2800			
		.025 4.1500						.035 4.2850			
		.030 4.1550						.040 4.2900			
		.035 4.1600						.060 4.3100			
		.040 4.1650						.065 4.3150			
		.045 4.1700						.125 4.3750			
		.060 4.1850				C5541	8	Std. 4.2500	1/16, 1/16, 3/16	7	Std.
SN8580	8	Std. 4.1250	1/16, 1/16, 3/16	PVD	Reduced			.020 4.2700			
		.005 4.1300						.030 4.2800			
		.035 4.1600						.040 4.2900			
		.045 4.1700						.060 4.3100			
		.065 4.1900				CM5541	8	Std. 4.2500	1/16, 1/16, 3/16	8	Std.
2M5543	8	Std. 4.1510	1/16, 1/16, 3/16	1	Std.			.020 4.2700			
		.005 4.1550						.030 4.2800			
		.030 4.1800						.040 4.2900			
		.035 4.1850						.060 4.3100			
		.045 4.1950				2M8562	8	Std. 4.2500	1/16, 1/16, 3/16	6	Std.
		.065 4.2150						.005 4.2550			
2M5542	8	Std. 4.1650	1/16, 1/16, 3/16	1	Std.			.030 4.2800			

Style

Top

2nd

Oil

- 1 Ductile Iron, Torsional, Plasma Moly
- 2 Ductile Iron, Barrel Face, Chrome Plated
- 3 Steel, Torsional, Plasma Moly
- 4 Steel, Torsional, Plasma Moly
- 5 Steel, Barrel Face, Chrome Plated
- 6 Ductile Iron, Torsional, Plasma Moly
- 7 CLAIMER Cast Iron, Torsional, Phosphate Coated
- 8 CLAIMER Cast Iron, Torsional, Plasma Moly

- Cast Iron, Reverse Twist Torsional
- Cast Iron, Reverse Twist Torsional
- Cast Iron, Reverse Twist Torsional
- Cast Iron, Napier
- Cast Iron, Reverse Twist Torsional
- Ductile Iron, Napier
- Cast Iron, Reverse Twist Torsional
- Cast Iron, Reverse Twist Torsional

- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent



HASTINGS TOUGH GUY RACING RINGS by Diameter

SET NO.	CYL.	DIAMETER	RING WIDTHS	STYLE	OIL RING TENSION	SET NO.	CYL.	DIAMETER	RING WIDTHS	STYLE	OIL RING TENSION
		.035 4.2850				CM5580	8	Std. 4.5000	1/16, 1/16, 3/16	8	Std.
		.040 4.2900						.030 4.5300			
		.045 4.2950						.060 4.5600			
		.060 4.3100				2M5589	8	Std. 4.5000	1/16, 1/16, 3/16	1	Std.
		.065 4.3150						.005 4.5050			
2M5515	8	Std. 4.2500	1/16, 1/16, 3/16	1	Low			.025 4.5250			
		.030 4.2800						.030 4.5300			
		.035 4.2850						.035 4.5350			
		.060 4.3100						.045 4.5450			
		.065 4.3150						.060 4.5600			
SN8585	8	.125 4.3750	1/16, 1/16, 3/16	PVD	Reduced			.065 4.5650			
		Std. 4.2500						.100 4.6000			
		.005 4.2550				2M5596	8	Std. 4.5000	1/16, 1/16, 3/16	1	Low
		.035 4.2850						.005 4.5050			
		.045 4.2950						.025 4.5250			
CM5574	8	.065 4.3150	1/16, 1/16, 3/16	8	Std.			.030 4.5300			
		Std. 4.3200						.035 4.5350			
		.020 4.3400						.045 4.5450			
		.030 4.3500						.060 4.5600			
		.040 4.3600						.065 4.5650			
2M5528	8	.060 4.3800	1/16, 1/16, 3/16	1	Std.			.100 4.6000			
		Std. 4.3200				2M8588	8	Std. 4.5000	1/16, 1/16, 3/16	6	Std.
		.005 4.3250						.005 4.5050			
		.020 4.3400						.035 4.5350			
		.025 4.3450						.045 4.5450			
		.030 4.3500						.065 4.5650			
		.035 4.3550				SN8590	8	Std. 4.5000	1/16, 1/16, 3/16	PVD	Reduced
		.040 4.3600						.005 4.5050			
		.055 4.3750						.035 4.5350			
		.060 4.3800						.045 4.5450			
2M5520	8	.065 4.3850	1/16, 1/16, 3/16	1	Low			.065 4.5650			
		Std. 4.3200						.105 4.6050			
		.030 4.3500				SN8595	8	Std. 4.6250	1/16, 1/16, 3/16	PVD	Reduced
		.035 4.3550						.005 4.6300			
2M5577	8	Std. 4.3425	1/16, 1/16, 3/16	1	Std.						
		.033 4.3750									
		.040 4.3825									
		.060 4.4025									
CM5576	8	Std. 4.3600	1/16, 1/16, 3/16	8	Std.						
		.020 4.3800									
		.030 4.3900									
		.040 4.4000									
		.080 4.4400									
		.100 4.4600									
2M5536	8	Std. 4.3600	1/16, 1/16, 3/16	1	Std.						
		.020 4.3800									
		.024 4.3850									
		.030 4.3900									
		.035 4.3950									
		.040 4.4000									
		.065 4.4250									
		.080 4.4400									
		.085 4.4450									
2M5537	8	Std. 4.4675	1/16, 1/16, 3/16	1	Std.						
		.004 4.4700									
SM8582	8	Std. 4.5000	.043, .043, 3.0	4	Std.						
		.035 4.5350									
		.065 4.5650									
2M8525	8	Std. 4.5000	1.5, 1.5, 3.0	1	Std.						
		.100 4.6000									



Style

- 1 Ductile Iron, Torsional, Plasma Moly
- 2 Ductile Iron, Barrel Face, Chrome Plated
- 3 Steel, Torsional, Plasma Moly
- 4 Steel, Torsional, Plasma Moly
- 5 Steel, Barrel Face, Chrome Plated
- 6 Ductile Iron, Torsional, Plasma Moly
- 7 CLAIMER Cast Iron, Torsional, Phosphate Coated
- 8 CLAIMER Cast Iron, Torsional, Plasma Moly

2nd

- Cast Iron, Reverse Twist Torsional
- Cast Iron, Reverse Twist Torsional
- Cast Iron, Reverse Twist Torsional
- Cast Iron, Napier
- Cast Iron, Reverse Twist Torsional
- Ductile iron, Napier
- Cast Iron, Reverse Twist Torsional
- Cast Iron, Reverse Twist Torsional

Oil

- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent
- Hastings Patented Flex-Vent

CALL 269-945-2491
800-776-1088

432

Visit us at www.hastingsracing.com